



Casing

Injecting

Flowing



WELLSTRONG® REDBOX®



WELLSTRONG® BLUEBOX®



FLOWSTRONG® YELLOWBOX®



FLOWSTRONG® GREENBOX®

One Source with a complete spectrum of non-corrosive composite pipe solutions for Chemical, Industrial and Municipal Well Applications.




FUTURE PIPE INDUSTRIES

www.futurepipe.com

FLOWSTRONG® YELLOWBOX®

Our Flowstrong® Yellowbox® product line pertains to all diameters and pressures utilized in line pipe applications. Flowstrong® Yellowbox® line pipe is a machine-made composite material produced by filament winding high strength continuous glass fibers and corrosion resistant epoxy resin, specially formulated to result in a structurally and chemically optimum product.

 DIAMETER
50 mm – 450 mm


 Pressure
Up to 241 bar



Diameter	Max rated pressure (psig)	Diameter	Max rated pressure (psig)
2"	500-3500 psi	8"	500-2250 psi
2.5"	500-3250 psi	10"	500-2000 psi
3"	500-3250 psi	10L	500-1750 psi
3.5"	500-3250 psi	12"	500-1500 psi
4"	500-2750 psi	14.5"	500-1500 psi
5"	500-2500 psi	16.5"	500-1500 psi
6"	500-2500 psi	18"	500-1250 psi
6L"	500-2250 psi	24"	500-000 psi

FLOWSTRONG® GREENBOX®

Flowstrong® Greenbox® product consists of the Flowstrong® Yellowbox® product with an inner Nexus® liner to achieve more chemical resistance. The green box product are available with the Integral Joint connection type only.


 DIAMETER
50 mm – 450 mm

 Pressure
Up to 241 bar



WELLSTRONG® REDBOX®

Wellstrong® Redbox® down-hole tubing and casing is a machine-made composite product with enhanced tensile properties produced by the filament winding method. Wellstrong® Redbox® tubing and casing is used in injection and production wells throughout the oil field in any environment involving corrosive or otherwise aggressive fluids.

 DIAMETER
50 mm – 450 mm


 Pressure
Up to 241 bar



Diameter	Max rated pressure (psig)	Diameter	Max rated pressure (psig)
2 3/8"	1000-3500 psi	9 5/8"	1000-2500 psi
2 7/8"	1000-3250 psi	10 3/4"	1000-2500 psi
3 1/2"	1000-3250 psi	11 3/4"	1000-1750 psi
4"	1000-3250 psi	13 3/8"	1000-1750 psi
4 1/2"	1000-3000 psi	16"	1000-1750 psi
5 1/2"	1000-3000 psi	18"	1000-1500 psi
6 5/8"	1000-2750 psi	20"	1000-1500 psi
7"	1000-1750 psi	24"	1000-1250 psi
7 5/8"	1000-2750 psi		

WELLSTRONG® BLUEBOX®

Our Wellstrong® Bluebox® down-hole products is specially designed and formulated to provide an exceptionally high chemical corrosion resistance while maintaining the same mechanical strengths and capacities of the Wellstrong® Redbox® product line. Its primary utilization is in the chemical industry, particularly for injection tubing and casing in highly corrosive chemical disposal wells. Wellstrong® Bluebox® tubing and casing is available with the Integral Joint (IJ) connection type only.

 DIAMETER
50 mm – 450 mm

 Pressure
Up to 241 bar



11905 Proctor Road, Houston,
Texas 77038
United States of America
Tel: +1 281 847 2987
Fax: +1 281 847 4216

15915 Perkins Road
Baton Rouge, Louisiana 70810-3630
United States of America
Tel: +1 225 752 2705
Fax: +1 225 752 2757

Email: sales-usa@futurepipe.com